

## 30" DUAL ZONE WINE COLUMN WITH STAINLESS GLASS DOOR

## TR-30DZW-R/L-SG-C

TR-30DZW-R-SG-C (Right hinged)

TR-30DZW-L-SG-C (Left hinged)

## FEATURES

- Environmentally friendly, R600a hydrocarbon refrigerant that improves performance and efficiency while ensuring quiet operation.
- Industry exclusive, 300-series stainless steel interior and exterior.
- All stainless steel, beautifully crafted proud hinges pass True's rigorous one million door opening test.
- Beautifully crafted solid stainless steel door with 120° stayopen feature and ergonomically designed, robust, tubular handle.
- Commercially inspired lift-up grill on top of the unit with toe kick that complements the look of True's undercounter units.
- Patented TruLumina<sup>®</sup> LED lighting gently illuminates your product and allows you to choose from 14 different color options with the push of a button.
- Low-E, double pane, UV tinted glass.
- Intuitive True Precision<sup>®</sup> Control and readout provides digital accuracy and easy operation.
- 2 independent zones with dual evaporators that can be adjusted from 40°F (4.4°C) to 65°F (18.3°C).
- Full extension wine racks with unfinished cherry fronts that cradle your wine and prevent vibration.
- Display shelf that proudly displays your collection along with additional storage behind display.
- Optional Lock available must be ordered from factory.

## ORGANIZATION

• 15 full-extension, soft-close wine racks - 150 bottles.

## BUILD YOUR TRUE

Customize your True with a variety of finish and hardware options at **true-residential.com/custom**.





TR-30DZW-R-SG-C

# SPECIFICATIONS

Dimensions (w x h x d)	30" x 84" x 24"
Cutout Dimensions (w x h x d) Flush Opening Standard Opening	30¼" x 84¼" x 26" 29¾" x 84" x 24"
Capacity (cu. ft.)	20.6 × 150
Temperature Range	2 independent zones that can be adjust- ed from 40°F (4.4°C) to 65°F (18.3°C).
Weight (Ibs.)	TBD
Voltage	115/60/1 (115/60/1 NEMA-5-15R
Amps	1.2
Annual Energy Consumption (kwh)	400
Power Cord Length (ft.)	9
Energy Star Rated	_

2001 East Terra Lane | O'Fallon, MO 63366-4434 | p636.240.2400 | f636.272.7546 | true-residential.com | info@true-residential.com

Specifications subject to change without notice.



20 11/16" [525mm] -

55 1/4"

[1403mm]


31 15/32" [799mm]

29 15/32" [748mm]

135

5.

### 30 15/32" [774mm] TR-30DZW-R/L-SG-C 2 9/16" 27 29/32" [65mm] 709mm 30" [762mm] 25 25/32" 655mm 29 9/16" [751mm] 83 15/16" 67 29/32" [1725mm] [2132mm] 23 25/32" DOOR HEIGHT [604mm] 72 5/8" [1845mm] 3 15/16" [100mm] Ŧ FRONT SIDE ТОР **OPENING DIMENSIONS** ELECTRICAL LOCATED 5. 8 **FLUSH OPENING** WIDTH HEIGHT DEPTH ТОР 30¼" 84¼" 26" STANDARD OPENING 5/32" mm] D INSTA WIDTH HEIGHT DEPTH 84" 29¾" 24"



### **MODEL OPTIONS**

MODEL	FINISH
TR-30DZW-R-SG-C	Stainless glass door right-hinged
TR-30DZW-L-SG-C	Stainless glass door left-hinged

## **ACCESSORIES (OPTIONAL)**

Joining kit	
Side panel(s)	
Full size anti-condensation pad	
Optional Lock – must be ordered from factory.	

# WARRANTY

3 year full (parts & labor) 6 year sealed system (parts & labor) 7-12 year (parts only - sealed system on registered products)

Specifications subject to change without notice.